

# SPHERE

An exceptional field of vision of 180°. The easy to rise headgear and brow guard are adjustable for both height and depth and the SPHERE adapts itself to any situation for any use.



355 g



SPHERPI



FASHERPI



FASHERWPC3












FASHERWPC5  
*Discontinued product*

- + ULTRA ENVELOPING 20,5 CM X 39,4 CM X 0,18 CM**
- + ADJUSTABLE HEADGEAR AND BROW GUARD**
- + PC FLIP-UP FACE SHIELD**

**bolle**  
SAFETY

# SPHERE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>SPHERE</b>	 Polycarbonate	SPHERPI	2C-1,2  1 AT 8 9 C€	 EN166 3 8 9 AT C€	-
	 Polycarbonate	FASPIHERPI	2C-1.2  1 AT 8 9 C€	-	-
	 Welding Shade 3	FASPIHEREWPCC3	3  1 BT 9 C€	-	-
<i>Discontinued product</i>	 Welding Shade 5	FASPIHEREWPCC5	5  1 BT 9 C€	-	-

## LENS MARKING

### Optical class symbols:

1. Continuous work

### Use symbols:

8. Electrical short circuit arc

9. Molten metal and hot solids

### Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

A. High energy impact, resists a 6 mm, 0.86 g ball at 190 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

### Others symbols:

C€ European standard  Manufacturer name

## FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.


3. Liquid droplets or splashes.

8. Electrical short circuit arc

9. Molten metal and hot solids

A. High energy impact, resists a 6 mm, 0.86 g ball at 190 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

	PACKAGING AND EAN 13 CODE			<i>Discontinued product</i>
	SPHERPI	FASPIHERPI	FASPIHEREWPCC3	FASPIHEREWPCC5
Individual packaging	3660740001186	3660740001193	3660740007089	3660740007096
5 face shields per outer pack - 50 spare lenses per outer pack	3660740201180	3660740201197	3660740207083	3660740207090

CHARACTERISTICS	
LENSES	PC - 2.0 mm
FRAME	PP
TEMPLES	Non applicable
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	PI, WPCC3



17/10/2019

Europe Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle-safety.com**

**bolle**  
SAFETY