

FLIP-UP FACESHIELD

ULTRA PROTECTION & LIGHTNESS

Users will be thrilled by the lightness and design of this flip front protector. The RELRSI version is anti-fog acetate with a thickness of 1.5 mm that will protect you against short circuit electric arcs.

SUPPLIED WITH : Protective bag

 200 G

+ **PROTECTION AGAINST ELECTRICAL SHORT CIRCUIT ARCS (RELRSI VERSION)**

+ **19 X 29 CM TILTING SHIELD**

+ **ANTI-FOG COATING DEPENDING ON THE VERSION**



TECHNOLOGIES

PLATINUM LITE

VERSIONS



RELPSI



RELRSI



FARELPSI



FARELRSI

bolle
SAFETY



CERTIFIED
FOR EXPLOSIVE
ATMOSPHERES
ATEX IIA, IIA, IIB, IIC,
AREA 1,2,20,21,22

FLIP-UP FACESHIELD

| USE | VERSION | REFERENCE | LENS MARKING | FRAME MARKING | COATING | STANDARD |
|-----|----------------|-----------|-------------------|----------------|---------------|-------------|
| h | CLEAR -PC | RELPSI | 1FC€ | EN166 3 B 8 C€ | PLATINUM LITE | EN166-EN170 |
| h | CLEAR -ACETATE | RELRSI | 2C-1.2 2 B 8 N C€ | EN166 3 B 8 C€ | ANTI-FOG | EN166-EN170 |
| h | CLEAR -PC | FARELPSI | 1FC€ | | PLATINUM LITE | EN166-EN170 |
| h | CLEAR -ACETATE | FAELRSI | 2C-1.2 2 B 8 N C€ | | ANTI-FOG | EN166-EN170 |

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO C€ STANDARDS WILL BE SENT ON REQUEST.

PACKAGING & EAN13 CODE

| SINGLE: Size: 24 x 18 x 9 mm | INNER BOX: Size: xx cm Weight: kg | OUTER PACK: Size: 60 x 50 x 38 cm Weight: 12.25 kg |
|---------------------------------|---|--|
| 3660740003487 | 3660740103507 -1 pcs | 3660740203504 -50 pcs |
| 3660740001957 | 3660740101954 -1 pcs | 3660740201951 -50 pcs |
| 3660740003494 | 3660740103491 -25 pcs | 3660740203498 -250 pcs |
| 3660740001520 | 3660740101527 -25 pcs | 3660740201524 -200 pcs |
| CUSTOM CODE: 3926909790 | | |



CERTIFIED FOR EXPLOSIVE ATMOSPHERES
ATEX II, III, IIB, IIC, AREA 1.2, 20, 21, 22

GENERAL SPECIFICATIONS

| | | | |
|-------|----------------------|----------|--|
| LENS | POLYCARBONATE - 1 MM | FOAM | |
| CURVE | | STRAP | |
| FRAME | PP | OPTIONAL | |



KNOW MORE ABOUT MARKINGS:

OR SCAN:

CLEANING & STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



MADE IN: TW

DATASHEET: 09-11-2023

bolle-safety.com

Europe Headquarters
34 rue de la Soie
69100 Villeurbanne
France
P : 00 33 (0) 4 78 85 23 64

U.K. & Ireland
Unit C83- Barwell Business Park
Leatherhead Road - Chessington
Surrey - KT9 2NY - UK
P : 00 44 (0)208 391 4700

USA Office
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
United States of America
P : 800 222 6553

Asia-Pacific Office
32-40 Fairchild Street
Heatherton VIC 3202
Australia
P : 1300 138 098



THE PPE EYEWEAR SPECIALISTS